



Description

Outdoor luminary PANSY shines with the usage of highly-efficient LED lights sources. Its case and body are made from aluminium cast. Its transparent polycarbonate diffuser has high protection against mechanical impact IK09. PANSY luminary has also high ingress protection IP66, which classifies it as resistant to any kind of weather, so it keeps its primary, aesthetic and clean appearance during exploitation. PANSY is recommended for parks, gardens, plazas, market squares or other open spaces.

Basic information

Family: PANSY OD
Product: PANSY OD IP66 ANT 740 38 D480
Index: BLS0000002308
Pictograms:




Lighting and electrical parameters

Light source	LED
Luminous flux LED [lm]	4210
LED power [W]	21.8
Luminaire luminous flux [lm]	3834
Power of luminaire [W]	27
Luminaire's light efficiency [lm/W]	142
Color of the light [K]	4000
CRI	>70
SDCM (LED sources)	3
Protection against electric shock	I
Protection degree	ip66
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	72000
Lx/By	L70/B10
Operating temperature range [°C]	-25 ÷ 30
Driver	LED Driver

Mechanical parameters:

Assembly	mounted on poles
Material	aluminium
Color	anodized aluminium
Diffuser	ST transparent glass
Impact resistant	IK09
Weight [kg]	7.4
Dimensions [mm]	Ø479 x 525



A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024