ORCHID N LINIA



 Description
Surface-mounted luminary ORCHID is made out of anodized aluminium profile. ORCHID luminary is recommended for: office spaces, schools, universities or public administration buildings etc.

Basic information

ORCHID N LINIA Family: Product: ORCHID N MPRM ALU 830 LINIA-EP 47 1130 Index: BLS000002690 Pictograms:



Lighting and electrical parameters


Light source	LED
Luminous flux LED [lm]	5734
LED power [W]	34
Luminaire luminous flux [lm]	4722
Power of luminaire [W]	36
Luminaire's light efficiency [lm/W]	131
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RGO
Protection against electric shock	I.
Protection degree	IP44
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
Operating temperature range [°C]	5÷30
Driver	LED Driver

Mechanical parameters:

Dimensions [mm]	1130 x 60 x 72
Impact resistant	IK06
Diffuser	MPRM microprism
Color	anodized aluminium
Material	aluminium
Assembly	ceiling mounted



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 14-05-2024

Accessories

Index	BLS000003401
Name	ORCHID N / GK SPINACZ OPRAW LINIA

