



HONEY HONEYCOMB

Description

Modern architectural luminaire HONEYCOMB (hexagon) features an original pattern of the simple form. HONEY COMB luminaire is designed to interiors that require demanding architectural solutions. The shape of this luminaire is modelled on actual honeycomb cell (hexagon with curved finishes). It is perfect for hotel atriums, office receptions, architectural ateliers, conference rooms, corridors, halls in exclusive buildings and also cinemas, theatres or new-style shops in shopping centres.

Basic information

Family:	HONEY HONEYCOMB
Product:	HONEY HONEYCOMB Z PLX DALI WH 830 ZAW-1,5M 14 650
Index:	BLS0000002843
Pictograms:	




Lighting and electrical parameters

Light source	LED
Luminous flux LED [lm]	2840
LED power [W]	21
Luminaire luminous flux [lm]	1496
Power of luminaire [W]	25
Luminaire's light efficiency [lm/W]	60
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP54
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DALI Driver

Mechanical parameters:

Assembly	pendant
Material	aluminium
Color	white
Diffuser	PLX opalized
Impact resistant	IK04
Dimensions [mm]	650 x 592 x 85



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 08-05-2024