




Description

Surface-mounted luminary ORCHID K is made out of anodized aluminium profile and can be alternatively adjusted to be installed on the wall. The luminary is recommended to bathrooms or corridors.

Basic information

Family: ORCHID K  
Product: ORCHID K PLX IP44 DALI ALU 830 16 575  
Index: BLS0000003095  
Pictograms:




Lighting and electrical parameters


Light source	LED
Luminaire luminous flux [lm]	1633
Power of luminaire [W]	13.6
Luminaire's light efficiency [lm/W]	120
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
Operating temperature range [°C]	5 ÷ 30
Driver	DALI driver

Mechanical parameters:

Assembly	wall-mounted
Material	aluminum
Color	anodized aluminum
Diffuser	PLX opalized
Impact resistant	IK06
Weight [kg]	1.30
Dimensions [mm]	575 x 60 x 64



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.  
Date of last update: 18-08-2025