



ORCHID N LINIA

Description

Surface-mounted luminaire ORCHID is made out of anodized aluminium profile. ORCHID luminaire is recommended for: office spaces, schools, universities or public administration buildings etc.

Basic information

| | |
|-------------|--------------------------------------|
| Family: | ORCHID N LINIA |
| Product: | ORCHID N PLX ALU 830 LINIA-S 16 1122 |
| Index: | BLS0000003021 |
| Pictograms: | |



Lighting and electrical parameters

| | |
|--|---------------------|
| Light source | LED |
| Luminaire luminous flux [lm] | 1661 |
| Power of luminaire [W] | 13.2 |
| Luminaire's light efficiency [lm/W] | 126 |
| Color of the light [K] | 3000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | I |
| Protection degree | IP44 |
| Voltage | 220-240 V, 50-60 Hz |
| Lifetime of LED sources [h] | 150000 |
| Lx/By | L80/B50 |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | LED driver |

Mechanical parameters:

| | |
|------------------------|-----------------------|
| Assembly | ceiling mounted |
| Material | aluminum |
| Color | anodized aluminum |
| Diffuser | PLX opalized |
| Impact resistant | IK06 |
| Dimensions [mm] | 1122 x 60 x 72 |



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 01-08-2025