



Description

Suspension luminaire ORCHID is made out of anodized aluminium profile. ORCHID luminaire is recommended for: office spaces, schools, universities or public administration buildings etc.

Basic information

Family: ORCHID PZ
Product: ORCHID PZ-1,5m MPRM DALI ALU 840 18 575
Index: BLS0000003828
Pictograms:



Lighting and electrical parameters

Light source	LED
Luminous flux LED [lm]	2242
LED power [W]	11
Luminaire luminous flux [lm]	1846
Power of luminaire [W]	13
Luminaire's light efficiency [lm/W]	142
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
Operating temperature range [°C]	5 ÷ 30
Driver	DALI Driver

Mechanical parameters:

Assembly	pendant - slings required
Material	aluminium
Color	anodized aluminium
Diffuser	MPRM microprism
Impact resistant	IK06
Weight [kg]	1.3
Dimensions [mm]	575 x 60 x 72



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024

Accessories

Index	BLS0000003999
Name	Zawieszenie Typ 1 - Rozeta SQ pod zasilanie GR 1,5m



Index	BLS0000003940
Name	Zawieszenie Typ 2 - Rozeta SQ bez zasilania GR 1,5m



Index	BLS0000003959
Name	Zawieszenie Typ 6 - Prosty uchwyty sufitowy bez zasilania 1,5m

