



Description

Industrial luminaires ASTER is a ceiling luminary. It features high ingress protection (IP65) and high protection against mechanical impact (IK08). ASTER luminary is well-adjusted to dusty rooms or those with elevated humidity. ASTER luminaires are intended for rooms, such as halls, magazines, warehouses, subways, underground parking lots etc. ASTER should be exploited in temperature between -20°C and +40°C.

Basic information

Family: **ASTER C**
Product: **ASTER C N PC OPAL IP65 840 42 1200**
Index: **BLS0000004581**
Pictograms:




Lighting and electrical parameters

Light source	LED
Luminaire luminous flux [lm]	4200
Power of luminaire [W]	40
Luminaire's light efficiency [lm/W]	105
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	4
Beam angle [°]	115
Protection against electric shock	I
Protection degree	IP65
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	70000
Lx/By	L70/B50
Operating temperature range [°C]	-20 - +40
Driver	LED Driver

Mechanical parameters:

Assembly	ceiling mounted
Material	polycarbonate
Color	gray
Diffuser	PC opalized polycarbonate
Impact resistant	IK10
Weight [kg]	1.24
Dimensions [mm]	1190 x 72 x 61



A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024