



Description

HOYA luminaire is built from rectangular aluminium profiles that are galvanized. Simple flat shape creates elegantly presenting architectural element. Used LED light sources in this luminaire enables to realize majority of the projects. Application: paths in gardens/parks, entrances to the properties, public spaces.

Basic information

Family: HOYA L Mini
Product: HOYA L G MINI IP54 ANT 840 13 1000x100x40
Index: BLS0000004755
Pictograms:




Lighting and electrical parameters

Light source	LED
Luminaire luminous flux [lm]	1333
Power of luminaire [W]	14
Luminaire's light efficiency [lm/W]	95
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP54
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	- 30 ÷ +30
Driver	LED driver
Circuit load capacity	B10 - 8 B13 - 11 B16 - 13

Mechanical parameters:

Assembly	ground-mounted
Material	aluminum
Color	anthracite
Impact resistant	IK10
Dimensions [mm]	1000 x 100 x 40



A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 18-08-2025

Accessories

Index	BLS0000005918
Name	Fundament maly 15kg

