

Description

Outdoor architectural luminaire NEMESIA. The body of NEMESIA is made from aluminium and is lacquered in specialistic facade paint that is resistant to any kind of weather. Different LED colours are also possible. NEMESIA luminaire is highly energy-efficient thanks to its high-performance components. Its ergonomic and functional shape enables to use of NEMESIA in practically every kind of building. The assembly and access to the inside is very easy. It is ideal to emphasize the character of the building, it plays a role of secondary lighting, which makes NEMESIA a great outdoor lighting decoration with a simple form and aesthetic look.

Basic information

Family:	NEMESIA N IP54
Product:	NEMESIA OD N PLX IP54 WH 840 16 150x150x150
Index:	BLS0000004816
Pictograms:	




Lighting and electrical parameters

Light source	LED wbudowany
Luminaire luminous flux [lm]	1776
Power of luminaire [W]	20
Luminaire's light efficiency [lm/W]	89
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP54
Voltage	220-240V
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	-25 ÷ 30
Driver	LED driver

Mechanical parameters:

Assembly	ceiling mounted
Material	aluminum
Color	white
Diffuser	PLX opalized
Dimensions [mm]	150 x 150 x 150



A graph of light