

Description



Basic information

Family: ORCHID STAR
Product: ORCHID STAR PRO PZ-1,5m MPRM DALI BL - ALU 830 16 1160
Index: BLS0000005356
Pictograms:



Lighting and electrical parameters

Light source	LED
Luminous flux LED [lm]	2083
LED power [W]	10.9
Luminaire luminous flux [lm]	1638
Power of luminaire [W]	12.4
Luminaire's light efficiency [lm/W]	132
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DALI Driver

Mechanical parameters:

Assembly	pendant
Material	aluminium
Color	side black - body anodized aluminium
Diffuser	MPRM microprism
Impact resistant	IK06
Dimensions [mm]	1160 x 62 x 105



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 08-05-2024

Accessories

Index	BLS0000003998
Name	Zawieszenie Typ 1 - Różeta SQ pod zasilanie BL 1,5m



Index	BLS0000003939
Name	Zawieszenie Typ 2 - Różeta SQ bez zasilania BL 1,5m



Index	BLS0000003959
Name	Zawieszenie Typ 6 - Prosty uchwyt sufitowy bez zasilania 1,5m

