Product card

ROSE P CLIP-IN



Description

CLEAN luminary ROSE is intended for module dropped ceilings and is made out of whitelacquered steel plate. Application: operating theatre, doctors' surgery, laboratory.

Basic information

Family:
ROSE P CLIP-IN

Product:
ROSE P CLIP-IN MPRM IP65 WH 940 51 600

Index:
BLS000005557

Pictograms:
Filter State Sta




Lighting and electrical parameters


Light source	LED
Luminous flux LED [lm]	7203
LED power [W]	46.8
Luminaire luminous flux [lm]	5778
Power of luminaire [W]	50
Luminaire's light efficiency [Im/W]	116
Color of the light [K]	4000
CRI	>90
SDCM (LED sources)	3
Protection against electric shock	1
Protection degree	IP65
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L70/B50
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver

Mechanical parameters:

Assembly	recessed into clip-in ceiling
Material	steelsheet
Color	white
Diffuser	MPRM microprism
Impact resistant	IK04
Dimensions [mm]	595 x 595 x 80



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 25-04-2024

