



Description

Wall-mounted, decorative luminaire. Oblong tubular housing made of aluminum. The luminaire shines both up and down, illuminating the area near the wall and illuminating the entire room with the light reflected from the ceiling. Application: restaurants and cafes, representative receptions, lounges.

Basic information

Family: PEONY K
Product: PEONY K UD WH 840 18 800
Index: BLS0000005654
Pictograms:



Lighting and electrical parameters

| | |
|-------------------------------------|------------|
| LED power [W] | 14 |
| Luminaire luminous flux [lm] | 1980 |
| Power of luminaire [W] | 16 |
| Luminaire's light efficiency [lm/W] | 124 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 2 |
| Protection against electric shock | I |
| Protection degree | IP20 |
| Voltage | 220-240V |
| Lifetime of LED sources [h] | 100000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | LED Driver |

Mechanical parameters:

| | |
|------------------|--------------|
| Assembly | wall-mounted |
| Material | aluminium |
| Color | white |
| Impact resistant | IK04 |
| Dimensions [mm] | Ø40 x 800 |



A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024