

FREESIA HONEYCOMB GK

Description

Recessed-mounted luminairesFREESIA HONEYCOMB is equipped with the highly-efficient LED light sources. The body of the product is made from white powder-lacquered steel plate.

Basic information

Family:	FREESIA HONEYCOMB GK
Product:	FREESIA HONEYCOMB GK PLX IP44 BL 830 22 331
Index:	BLS0000005761
Pictograms:	




Lighting and electrical parameters

Light source	LED
Luminous flux LED [lm]	2860
LED power [W]	17
Luminaire luminous flux [lm]	2206
Power of luminaire [W]	18
Luminaire's light efficiency [lm/W]	123
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	II
Protection degree	IP44
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	100000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver

Mechanical parameters:

Assembly	recessed into the plasterboard ceiling
Material	aluminium
Color	black
Diffuser	PLX opalized
Impact resistant	IK04
Weight [kg]	1.1
Dimensions [mm]	330 x 85
Mounting hole [mm]	310 x 330



A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 25-04-2024