



Description

Surface-mounted luminary ORCHID C GK is made out of anodized aluminium profile. ORCHID luminary is recommended for: office spaces, schools, universities or public administration buildings etc.

Basic information

Family:	ORCHID C GK
Product:	ORCHID C GK PLX ALU 840 28 1135
Index:	BLS0000005900
Pictograms:	




Lighting and electrical parameters


Light source	LED
Luminous flux LED [lm]	4100
LED power [W]	29
Luminaire luminous flux [lm]	2880
Power of luminaire [W]	31
Luminaire's light efficiency [lm/W]	93
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	90000
Lx/By	L70/B10
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver

Mechanical parameters:

Assembly	recessed into raster ceiling
Material	aluminium
Color	anodized aluminium
Diffuser	PLX opalized
Impact resistant	IK06
Dimensions [mm]	1142 x 80 x 72
Mounting hole [mm]	1126 x 70



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 25-04-2024