PEONY K

Description

Wall-mounted, decorative luminaire. Oblong tubular housing made of aluminum. The luminaire shines both up and down, illuminating the area near the wall and illuminating the entire room with the light reflected from the ceiling. Application: restaurants and cafes, representative receptions, lounges.

Basic information

Family:	**PEONY K**
Product:	**PEONY K UD ANT 840 18 800**
Index:	**BLS0000006272**
Pictograms:	

Lighting and electrical parameters

Luminous flux LED [lm]	2090
LED power [W]	**14**
Luminaire luminous flux [lm]	1980
Power of luminaire [W]	**16**
Luminaire's light efficiency [lm/W]	124
Color of the light [K]	**4000**
CRI	>80
SDCM (LED sources)	**2**
Protection against electric shock	I
Protection degree	**IP20**
Voltage	220-240V
Lifetime of LED sources [h]	**100000**
Lx/By	L80/B10
Operating temperature range [°C]	**5 ÷ 30**
Driver	LED Driver

Mechanical parameters:

Assembly	wall-mounted
Material	**aluminium**
Color	black
Impact resistant	**IK04**
Dimensions [mm]	Ø40 x 800



Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 25-04-2024