


Description

Architectural Bee Art luminaire LOBELIA is a lighting luminaire that is equipped with the highly-efficient LED lighting sources. LOBELIA is made out of aluminium profile. LOBELIA luminaires are perfect to highlight the character of representative places; that have to maintain their elegant form, such as: entry area, receptions, restaurants, corridors etc.

Basic information

Family: **ORCHID N V**
Product: **ORCHID N V MPRM ALU 830 75 1200 1200**
Index: **BLS0000006697**
Pictograms:




Lighting and electrical parameters


Light source	LED
Luminaire luminous flux [lm]	7545
Power of luminaire [W]	54.4
Luminaire's light efficiency [lm/W]	139
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
Operating temperature range [°C]	5 ÷ 30
Driver	LED driver

Mechanical parameters:

Assembly	ceiling mounted
Material	aluminum
Color	anodized aluminum
Diffuser	MPRM micropism
Impact resistant	IK06
Dimensions [mm]	1145 1145 x 60 x 72



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 01-08-2025