


HOYA luminary is built from rectangular aluminium profiles that are galvanized. Simple flat shape creates elegantly presenting architectural element. Used LED light sources in this luminary enables to realize majority of the projects. Application: paths in gardens/parks, entrances to the properties, public spaces.

Family: **HOYA T**
 Product: **HOYA T G IP65 ANT 740 ST-S 2x39 3000x150x150**
 Index: **BLS0000006954**
 Pictograms:



Light source	LED
Luminous flux LED [lm]	8550
LED power [W]	47
Luminaire luminous flux [lm]	7872
Power of luminaire [W]	54
Luminaire's light efficiency [lm/W]	146
Color of the light [K]	4000
CRI	>70
SDCM (LED sources)	3
Protection against electric shock	I
Protection degree	IP65
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	72000
Lx/By	L70/B10
Operating temperature range [°C]	-40 ÷ 50
Driver	LED Driver


Assembly	ground
Material	aluminium
Color	anthracite
Diffuser	transparent glass lenses
Impact resistant	IK09
Dimensions [mm]	3000 x 150 x 150




Date of last update: 25-04-2024

Accessories

Index	BLS0000005917
Name	Fundament B50



Index	BLS0000009083
Name	Izolacyjne złącze bezpiecznikowe IZK-4-01



Index	BLS0000009053
Name	Komplet nakrętek montażowych słupa + kapturek maskujący czarnym - do B-50

