




Description

Surface-mounted luminaire ORCHID C GK is made out of anodized aluminium profile. ORCHID luminary is recommended for: office spaces, schools, universities or public administration buildings etc.

Basic information

Family:	ORCHID C GK
Product:	ORCHID C GK MPRM WH 840 32 1135
Index:	BLS0000007001
Pictograms:	




Lighting and electrical parameters


Light source	LED
Luminaire luminous flux [lm]	3230
Power of luminaire [W]	23.3
Luminaire's light efficiency [lm/W]	139
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	90000
Lx/By	L70/B10
Operating temperature range [°C]	5 ÷ 30
Driver	LED driver

Mechanical parameters:

Assembly	in the plasterboard ceiling
Material	aluminum
Color	white
Diffuser	MPRM micropism
Impact resistant	IK06
Dimensions [mm]	1142 x 80 x 72
Mounting hole [mm]	1126 x 70



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 18-08-2025