



Description

Surface-mounted luminary ORCHID C GK is made out of anodized aluminium profile. ORCHID luminary is recommended for: office spaces, schools, universities or public administration buildings etc.

Basic information

Family: ORCHID C GK
Product: ORCHID C GK MPRM BL 840 41 1135
Index: BLS0000007004
Pictograms:




Lighting and electrical parameters


Light source	LED
Luminous flux LED [lm]	5300
LED power [W]	39
Luminaire luminous flux [lm]	4146
Power of luminaire [W]	41
Luminaire's light efficiency [lm/W]	101
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	90000
Lx/By	L70/B10
Operating temperature range [°C]	5 ÷ 30
Driver	LED Driver

Mechanical parameters:

Assembly	recessed into raster ceiling
Material	aluminium
Color	black
Diffuser	MPRM microprism
Impact resistant	IK06
Dimensions [mm]	1142 x 80 x 72
Mounting hole [mm]	1126 x 70



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024