ORCHID C N



Description

Surface-mounted luminary ORCHID is made out of anodized aluminium profile. ORCHID luminary is recommended for: office spaces, schools, universities or public administration buildings etc.

Basic information

Family: ORCHID C N

Product: ORCHID C N PLX DALI BL 840 27 1135

Index: BL\$000007013

Pictograms:











■ Lighting and electrical parameters


Light source	LED
Luminaire luminous flux [lm]	2796
Power of luminaire [W]	23.3
Luminaire's light efficiency [lm/W]	120
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	1
Protection degree	IP44
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	90000
Lx/By	L70/B10
Operating temperature range [°C]	5÷30
Driver	DALI driver

Mechanical parameters:

Assembly	ceiling mounted
Material	aluminum
Color	black
Diffuser	PLX opalized
Impact resistant	IK06
Weight [kg]	1.95
Dimensions [mm]	1135 x 60 x 72



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 21-10-2025

