




## Description

## Basic information

Family:	<b>ORCHID PRO P</b>
Product:	<b>ORCHID PRO P MPRM WH 830 34 1195</b>
Index:	<b>BLS0000007241</b>
Pictograms:	



## Lighting and electrical parameters


Light source	LED
<b>Luminous flux LED [lm]</b>	<b>4166</b>
LED power [W]	21.8
<b>Luminaire luminous flux [lm]</b>	<b>3431</b>
Power of luminaire [W]	23.8
<b>Luminaire's light efficiency [lm/W]</b>	<b>144</b>
Color of the light [K]	3000
<b>CRI</b>	<b>&gt;80</b>
SDCM (LED sources)	3
<b>Photobiological risk class (IEC/EN 62471)</b>	<b>RG0</b>
Protection against electric shock	I
<b>Protection degree</b>	<b>IP44</b>
Voltage	220-240 V, 50-60 Hz
<b>Lifetime of LED sources [h]</b>	<b>150000</b>
Lx/By	L80/B10
<b>Operating temperature range [°C]</b>	<b>5 ÷ 30</b>
Driver	LED driver

## Mechanical parameters:

Assembly	recessed into the modular ceiling
<b>Material</b>	<b>aluminum</b>
Color	white
<b>Diffuser</b>	<b>MPRM microprism</b>
Impact resistant	IK06
<b>Dimensions [mm]</b>	<b>1195 x 80 x 72</b>



## A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 20-09-2024