NEMESIA OD K IP54_



Description

Basic information

Family: **NEMESIA OD K IP54_**

Product: NEMESIA OD K PLX IP54 BL 830 16 140x120x120

Index: **BLS000007449z**

Pictograms:










Lighting and electrical parameters

| Light source | LED wbudowany |
|---|---------------|
| Luminaire luminous flux [lm] | 1725 |
| Power of luminaire [W] | 20 |
| Luminaire's light efficiency [lm/W] | 86 |
| Color of the light [K] | 3000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | 1 |
| Protection degree | IP54 |
| Voltage | 220-240V |
| Lifetime of LED sources [h] | 100000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | -25÷30 |
| Driver | LED driver |
| | |

Mechanical parameters:

| Assembly | wall-mounted |
|-----------------|-----------------|
| Material | aluminum |
| Color | black |
| Diffuser | PLXopalized |
| Dimensions [mm] | 140 x 120 x 120 |



A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 01-08-2025

