

### Description

#### Basic information

Family: LILY SQ adj N

Product: LILY SQ adj N DALI BL 830 32 215

Index: **BLS000007474** 

Pictograms:











# **●** Lighting and electrical parameters


| Light source                              | LED               |
|---|-------------------|
| Luminaire luminous flux [lm]              | 3268              |
| Power of luminaire [W]                    | 27                |
| Luminaire's light efficiency [lm/W]       | 121               |
| Color of the light [K]                    | 3000              |
| CRI                                       | >80               |
| SDCM (LED sources)                        | 2                 |
| Photobiological risk class (IEC/EN 62471) | RG0               |
| Protection against electric shock         | II                |
| Protection degree                         | IP20              |
| Voltage                                   | 220-240V, 50-60Hz |
| Lifetime of LED sources [h]               | 100000            |
| Lx/By                                     | L80/B10           |
| Operating temperature range [°C]          | 5÷30              |
| Driver                                    | DALI driver       |

#### Mechanical parameters:

| Dimensions [mm]  | 215 x 215 x 17 0     |
|------------------|----------------------|
| Impact resistant | IK05                 |
| Diffuser         | ST transparent glass |
| Color            | black                |
| Material         | aluminum             |
| Assembly         | ceiling mounted      |
|                  |                      |



## A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 18-08-2025

