Product card

ROSE MED CLIP-IN

Description

Basic information

Family: **ROSE MED CLIP-IN**

Product: **ROSE MED P CLIP-IN MPRM SH DALI IP65 940 48 600**

Index: **BLS0000007573**

Pictograms:

Lighting and electrical parameters

Light source	LED
Luminous flux LED [lm]	**7203**
LED power [W]	46.8
Luminaire luminous flux [lm]	**5131**
Power of luminaire [W]	50
Luminaire's light efficiency [lm/W]	**103**
Color of the light [K]	4000
CRI	**>90**
SDCM (LED sources)	3
Protection against electric shock	**I**
Protection degree	IP65
Voltage	**220-240 V, 50-60 Hz**
Lifetime of LED sources [h]	150000
Lx/By	**L70/B50**
Operating temperature range [°C]	5 ÷ 30
Driver	**DALI Driver**

Mechanical parameters:

Assembly	recessed into clip-in ceiling
Material	**steel sheet + antibacterial paint**
Color	white
Diffuser	**MPRM SH microprism tempered glass**
Impact resistant	IK08
Dimensions [mm]	**595 x 595 x 80**



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 25-04-2024