
Product card

ORCHID N LINIA



Description

Surface-mounted luminary ORCHID is made out of anodized aluminium profile. ORCHID luminary is recommended for: office spaces, schools, universities or public administration buildings etc.

Basic information

Family:ORCHID N LINIAProduct:ORCHID N PLX ALU 830 LINIA-EL 481690Index:BLS000008097Pictograms:Filter State Sta




Lighting and electrical parameters


Light source	LED
Luminaire luminous flux [lm]	4899
Power of luminaire [W]	40.9
Luminaire's light efficiency [Im/W]	120
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RGO
Protection against electric shock	I
Protection degree	IP44
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
Operating temperature range [°C]	5÷30
Driver	LED driver

Mechanical parameters:

Assembly	ceiling mounted
Material	aluminum
Color	anodized aluminum
Diffuser	PLXopalized
Impact resistant	IK06
Dimensions [mm]	1690 x 60 x 72



A graph of light



cd/klm C0 - C180 _____C90 - C270

Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 01-08-2025

