

# **ORCHID N LINIA**

### Description

Surface-mounted luminary ORCHID is made out of anodized aluminium profile. ORCHID luminary is recommended for: office spaces, schools, universities or public administration buildings etc.

#### Basic information

Family: ORCHID N LINIA

Product: ORCHID N PLX BL 840 LINIA-S 51 1682

Index: BLS000008107

Pictograms:













# Lighting and electrical parameters


Light source	LED
Luminaire luminous flux [lm]	5187
Power of luminaire [W]	40.9
Luminaire's light efficiency [lm/W]	127
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	1
Protection degree	IP44
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
Operating temperature range [°C]	5÷30
Driver	LED driver

## Mechanical parameters:

Dimensions [mm]	1682 x 60 x 72
Impact resistant	IK06
Diffuser	PLXopalized
Color	black
Material	aluminum
Assembly	ceiling mounted



# A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 01-08-2025

