




## Description

Outdoor wide-beam LED floodlight. The luminaire is equipped with a motion sensor. The luminaire is intended for lighting car parks, outdoor areas and entrances in front of buildings.

## Basic information

Family:	<b>PUMPKIN</b>
Product:	<b>PUMPKIN CMW SH BL IP44 840 22 152</b>
Index:	<b>BLS0000008670</b>
Pictograms:	




## Lighting and electrical parameters

Light source	LED
<b>Luminaire luminous flux [lm]</b>	<b>2200</b>
Power of luminaire [W]	20
<b>Luminaire's light efficiency [lm/W]</b>	<b>110</b>
Color of the light [K]	4000
<b>CRI</b>	<b>&gt;80</b>
Beam angle [°]	120
<b>Protection against electric shock</b>	<b>I</b>
Protection degree	IP44
<b>Voltage</b>	<b>220-240V, 50-60Hz</b>
Lifetime of LED sources [h]	50000
<b>Lx/By</b>	<b>L70/B50</b>
Operating temperature range [°C]	- 20 ÷ +45
<b>Driver</b>	<b>LED driver</b>

## Mechanical parameters:

Assembly	wall-mounted
<b>Material</b>	<b>aluminum</b>
Color	black
<b>Diffuser</b>	<b>SH tempered glass</b>
Weight [kg]	0.37
<b>Dimensions [mm]</b>	<b>189 x 125 x 55</b>



## A graph of light

# Accessories

Index	BLS0000015166
Name	Złączka IP68 - THB.391.A3A 3P



Index	BLS0000015166
Name	Złączka IP68 - THB.391.A3A 3P

