

Description

Linear earth luminaire, made of aluminium. IP67, luminaire adapted for installation in vehicle driveways. Symmetrical lighting. Application - illumination of walls, plants, indicating directions in the pavement by line lighting.



Basic information

Family: SICURA 1836 Sym
Product: SICURA 1836 LED 43W CLD GREY
Index: BLS0000008705
Pictograms:




Lighting and electrical parameters

Light source	LED
Luminaire luminous flux [lm]	5905
Power of luminaire [W]	43
Luminaire's light efficiency [lm/W]	137
Color of the light [K]	4000
CRI	>80
Photobiological risk class (IEC/EN 62471)	RG1
Protection against electric shock	II
Protection degree	IP67
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	50000
Lx/By	L80/B20
Operating temperature range [°C]	-30 ÷ 40
Driver	LED Driver

Mechanical parameters:

Assembly	ground
Material	aluminium
Color	anodized aluminium
Diffuser	SH tempered glass
Impact resistant	IK08
Weight [kg]	8.26
Dimensions [mm]	1210 x 100 x 100
Mounting hole [mm]	1195 x 95 x 95



A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 25-04-2024