



Description

Surface-mounted luminaire POPPY is made from polycarbonate. The ingress protection (IP54) and its hermetic construction enable POPPY to work in rooms and spaces that have elevated humidity. POPPY luminaire is classified to be used indoors, in places such as circulation areas, staircases etc.

Basic information

Family: POPPY O IP54
Product: POPPY O N IP54 840 30/36 D330
Index: BLS0000008864
Pictograms:




Lighting and electrical parameters


Light source	LED
Luminaire luminous flux [lm]	3000 / 3600
Power of luminaire [W]	28 / 36
Luminaire's light efficiency [lm/W]	107 / 100
Color of the light [K]	4000
CRI	>80
Protection against electric shock	II
Protection degree	IP54
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	70000
Lx/By	L70/B50
Driver	LED driver
LED driver settings	840: 3600 lm - 36 W 840: 3000 lm - 28 W

Mechanical parameters:

Assembly	ceiling mounted
Material	polycarbonate
Color	gray
Diffuser	PC opalized polycarbonate
Impact resistant	IK10
Weight [kg]	0.90
Dimensions [mm]	Ø330 x 54



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 18-08-2025