



Description

POPPY surface mounted luminaire made of polycarbonate. Ingress protection level (IP54) and airtight structure allow for mounting in rooms with higher humidity. Dual-range luminaire with power settings of 12W or 15W set by manufacturer during assembly. POPPY is classified for indoor usage, in places like passageways or staircases.

Basic information

Family: **POPPY O IP54**  
Product: **POPPY O N IP54 CMW 840 30/36 D330**  
Index: **BLS0000008865**  
Pictograms:




Lighting and electrical parameters


Light source	LED
Luminaire luminous flux [lm]	3000 / 3600
Power of luminaire [W]	28 / 36
Luminaire's light efficiency [lm/W]	107 / 100
Color of the light [K]	4000
CRI	>80
Protection against electric shock	II
Protection degree	IP54
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	70000
Lx/By	L70/B50
Driver	LED driver
LED driver settings	840: 3600 lm - 36 W 840: 3000 lm - 28 W

Mechanical parameters:

Assembly	ceiling mounted
Material	polycarbonate
Color	gray
Diffuser	PC opalized polycarbonate
Impact resistant	IK10
Weight [kg]	0.90
Dimensions [mm]	Ø330 x 50



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.  
Date of last update: 18-08-2025