



Description

Architectural Bee Art luminary LOBELIA is a lighting luminary that is equipped with the highly-efficient LED lighting sources. LOBELIA is made out of aluminium profile. LOBELIA luminaires are perfect to highlight the character of representative places; that have to maintain their elegant form, such as: entry area, receptions, restaurants, corridors etc.

Basic information

Family:	ORCHID N L LINIA
Product:	ORCHID N L MPRM DALI ALU 840 LINIA-EL-S 36 600 600
Index:	BLS0000009710
Pictograms:	




Lighting and electrical parameters

Light source	LED
Luminous flux LED [lm]	4484
LED power [W]	23
Luminaire luminous flux [lm]	3693
Power of luminaire [W]	25
Luminaire's light efficiency [lm/W]	148
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
Operating temperature range [°C]	5 ÷ 30
Driver	DALI Driver

Mechanical parameters:

Assembly	ceiling mounted
Material	aluminium
Color	anodized aluminium
Diffuser	MPRM microprism
Impact resistant	IK06
Dimensions [mm]	598 595 x 60 x 72



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.  
Date of last update: 25-04-2024