
ORCHID N L LINIA



Description

Architectural Be Art luminary LOBELIA is a lighting luminary that is equipped with the highly-efficient LED lighting sources. LOBELIA is made out of aluminium profile. LOBELIA luminaries are perfect to highlight the character of representative places; that have to maintain their elegant form, such as: entry area, receptions, restaurants, corridors etc.

Basic information

Family: ORCHID N L LINIA

Product: ORCHID N L MPRM DALI ALU 840 LINIA-EP-S 73 1200 1200

Index: BLS000009934

Pictograms:












■ Lighting and electrical parameters


Light source	LED
Luminous flux LED [Im]	8968
LED power [W]	44
Luminaire luminous flux [lm]	7386
Power of luminaire [W]	48
Luminaire's light efficiency [lm/W]	154
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	1
Protection degree	IP44
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
Operating temperature range [°C]	5÷30
Driver	DALI Driver

Mechanical parameters:

Assembly	ceiling mounted
Material	aluminium
Color	anodized aluminium
Diffuser	MPRM microprism
Impact resistant	IK06
Dimensions [mm]	1158 1155 x 60 x 72



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 14-05-2024

