Product card

LILY SQ Mini P

⬢ Description

⬢ Basic information

Family: **LILY SQ Mini P**
Product: **LILY SQ Mini L2 P PLX BL 840 12 140x90**
Index: **BLS0000010347**
Pictograms:

⟨CE⟩ ⟨6Y⟩ ⟨▢⟩ ⟨IP20⟩ ⟨IK04⟩

⬢ Lighting and electrical parameters

Light source	LED
Luminaire luminous flux [lm]	**1227**
Power of luminaire [W]	14
Luminaire's light efficiency [lm/W]	**88**
Color of the light [K]	4000
CRI	**>80**
SDCM (LED sources)	3
Protection against electric shock	**II**
Protection degree	IP20
Voltage	**220-240V, 50-60Hz**
Lifetime of LED sources [h]	100000
Lx/By	**L80/B10**
Operating temperature range [°C]	5 ÷ 30
Driver	**LED driver**

⬢ Mechanical parameters:

Assembly	recessed into the modular and plasterboard ceiling
Material	**aluminum / steel sheet**
Color	black
Diffuser	**PLX opalized**
Impact resistant	IK04
Dimensions [mm]	**140 x 90 x 52**
Mounting hole [mm]	115 x 82

⬢ A graph of light

BEELIGHT