

Description



Basic information

Family: **SENECIO GRID K**  
Product: **SENECIO GRID OD K PLX IP54 WH 840 22 650x150x165**  
Index: **BLS0000010350**  
Pictograms:




Lighting and electrical parameters

Light source	LED
<b>Luminaire luminous flux [lm]</b>	<b>2287</b>
Power of luminaire [W]	25
<b>Luminaire's light efficiency [lm/W]</b>	<b>91</b>
Color of the light [K]	4000
<b>CRI</b>	<b>&gt;80</b>
SDCM (LED sources)	3
<b>Photobiological risk class (IEC/EN 62471)</b>	<b>RG0</b>
Protection against electric shock	I
<b>Protection degree</b>	<b>IP54</b>
Voltage	220–240V, 50–60Hz
<b>Lifetime of LED sources [h]</b>	<b>150000</b>
Lx/By	L80/B50
<b>Operating temperature range [°C]</b>	<b>– 30 ÷ 40</b>
Driver	LED driver

Mechanical parameters:

Assembly	wall-mounted
<b>Material</b>	<b>metal</b>
Color	white
<b>Diffuser</b>	<b>PLX opalized</b>
Impact resistant	IK04
<b>Dimensions [mm]</b>	<b>650 x 150 x 165</b>



A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality.  
Date of last update: 18-08-2025