



Description

Surface-mounted luminary ORCHID is made out of anodized aluminium profile. ORCHID luminary is recommended for: office spaces, schools, universities or public administration buildings etc.

Basic information

Family: ORCHID OD N
Product: ORCHID OD N-ML OPT-G IP54 BL 840 40 1135
Index: BLS0000010368
Pictograms:



Lighting and electrical parameters


Light source	LED
Luminaire luminous flux [lm]	4018
Power of luminaire [W]	22.4
Luminaire's light efficiency [lm/W]	179
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP54
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
Operating temperature range [°C]	-30 ÷ 40
Driver	LED driver

Mechanical parameters:

Assembly	ceiling mounted with magnets
Material	aluminum
Color	black
Diffuser	GARAGE optics
Impact resistant	IK06
Weight [kg]	1.95
Dimensions [mm]	1135 x 60 x 72



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 18-08-2025