



Description

Basic information

Family: TAGETES Raster III  
Product: TAGETES Raster III P 65st WH/BL 840 36 596  
Index: BLS0000010637  
Pictograms:




Lighting and electrical parameters

|                                     |                     |
|-------------------------------------|---------------------|
| Light source                        | LED                 |
| Luminous flux LED [lm]              | 4515                |
| LED power [W]                       | 23.2                |
| Luminaire luminous flux [lm]        | 3657                |
| Power of luminaire [W]              | 25                  |
| Luminaire's light efficiency [lm/W] | 146                 |
| Color of the light [K]              | 4000                |
| CRI                                 | >80                 |
| SDCM (LED sources)                  | 3                   |
| Protection against electric shock   | I                   |
| Protection degree                   | IP20                |
| Voltage                             | 220-240 V, 50-60 Hz |
| Lifetime of LED sources [h]         | 72000               |
| Lx/By                               | L80/B10             |
| Operating temperature range [°C]    | 5 ÷ 30              |
| Driver                              | LED Driver          |

Mechanical parameters:

|                  |                                   |
|------------------|-----------------------------------|
| Assembly         | recessed into the modular ceiling |
| Material         | steel sheet                       |
| Color            | white body, black raster          |
| Diffuser         | UGR 65° raster                    |
| Impact resistant | IK04                              |
| Dimensions [mm]  | 596 x 596 x 85                    |



A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality.  
Date of last update: 25-04-2024