


ORCHID Raster SLIM N

Description



Basic information

Family: ORCHID Raster SLIM N  
Product: ORCHID Raster SLIM N 65st WH 830 25 1135  
Index: BLS0000010726  
Pictograms:




Lighting and electrical parameters

|                                     |                     |
|-------------------------------------|---------------------|
| Light source                        | LED                 |
| Luminous flux LED [lm]              | 2850                |
| LED power [W]                       | 15                  |
| Luminaire luminous flux [lm]        | 2593                |
| Power of luminaire [W]              | 17                  |
| Luminaire's light efficiency [lm/W] | 153                 |
| Color of the light [K]              | 3000                |
| CRI                                 | >80                 |
| SDCM (LED sources)                  | 3                   |
| Protection against electric shock   | I                   |
| Protection degree                   | IP20                |
| Voltage                             | 220-240 V, 50-60 Hz |
| Lifetime of LED sources [h]         | 72000               |
| Lx/By                               | L80/B10             |
| Operating temperature range [°C]    | 5 ÷ 30              |
| Driver                              | LED Driver          |

Mechanical parameters:

|                  |                 |
|------------------|-----------------|
| Assembly         | ceiling mounted |
| Material         | aluminium       |
| Color            | white           |
| Diffuser         | UGR 65° raster  |
| Impact resistant | IK04            |
| Dimensions [mm]  | 1135 x 43 x 61  |



A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality.  
Date of last update: 25-04-2024