



Description

Surface-mounted luminary ORCHID SLIM is made out of anodized aluminium profile. ORCHID SLIM luminary is recommended for: office spaces, schools, universities, conference halls or public administration buildings etc.

Basic information

Family: ORCHID SLIM N
Product: ORCHID SLIM N PLX DALI ALU 840 34 1135
Index: BLS0000010872
Pictograms:




Lighting and electrical parameters

| | |
|---|---------------------|
| Light source | LED |
| Luminous flux LED [lm] | 5320 |
| LED power [W] | 28 |
| Luminaire luminous flux [lm] | 3431 |
| Power of luminaire [W] | 31 |
| Luminaire's light efficiency [lm/W] | 111 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | I |
| Protection degree | IP44 |
| Voltage | 220-240 V, 50-60 Hz |
| Lifetime of LED sources [h] | 150000 |
| Lx/By | L80/B50 |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | DALI Driver |

Mechanical parameters:

| | |
|------------------|--------------------|
| Assembly | ceiling mounted |
| Material | aluminium |
| Color | anodized aluminium |
| Diffuser | PLX opalized |
| Impact resistant | IK06 |
| Weight [kg] | 1.95 |
| Dimensions [mm] | 1135 x 43 x 61 |



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024