



Description

Surface-mounted luminaire ORCHID SLIM is made out of anodized aluminium profile. ORCHID SLIM luminaire is recommended for: office spaces, schools, universities, conference halls or public administration buildings etc.

Basic information

Family: ORCHID SLIM GK
Product: ORCHID SLIM GK PLX DALI ALU 840 33 1135
Index: BLS0000010896
Pictograms:




Lighting and electrical parameters


Light source	LED
Luminaire luminous flux [lm]	3319
Power of luminaire [W]	27.2
Luminaire's light efficiency [lm/W]	122
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
Operating temperature range [°C]	5 ÷ 30
Driver	DALI driver

Mechanical parameters:

Assembly	in the plasterboard ceiling
Material	aluminum
Color	anodized aluminum
Diffuser	PLX opalized
Impact resistant	IK06
Weight [kg]	1.95
Dimensions [mm]	1175 x 83 x 61
Mounting hole [mm]	1140 x 50



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 18-08-2025