ORCHID N



Description

Surface-mounted luminary ORCHID is made out of anodized aluminium profile. ORCHID luminary is recommended for: office spaces, schools, universities or public administration buildings etc.

Basic information

Family: ORCHID N

Product: ORCHID N PLX ALU 840 56 1695

Index: BL\$000011225

Pictograms:











● Lighting and electrical parameters


Light source	LED
Luminous flux LED [lm]	7576
LED power [W]	42
Luminaire luminous flux [lm]	5603
Power of luminaire [W]	46
Luminaire's light efficiency [lm/W]	122
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	1
Protection degree	IP44
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
Operating temperature range [°C]	5÷30
Driver	LED Driver

Mechanical parameters:

A India	111
Assembly	ceiling mounted
Material	aluminium
Color	anodized aluminium
Diffuser	PLXopalized
Impact resistant	IK06
Dimensions [mm]	1695 x 60 x 72



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 25-04-2024

