



Description

HOYA luminary is built from rectangular aluminium profiles that are galvanized. Simple flat shape creates elegantly presenting architectural element. Used LED light sources in this luminary enables to realize majority of the projects. Application: paths in gardens/parks, entrances to the properties, public spaces.

Basic information

Family:	HOYA T
Product:	HOYA T G IP65 ANT 740 ST-S 2x39 3000x150x100
Index:	BLS0000011743
Pictograms:	




Lighting and electrical parameters


Light source	LED
Luminous flux LED [lm]	8550
LED power [W]	47
Luminaire luminous flux [lm]	7872
Power of luminaire [W]	54
Luminaire's light efficiency [lm/W]	146
Color of the light [K]	4000
CRI	>70
SDCM (LED sources)	3
Protection against electric shock	I
Protection degree	IP65
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	72000
Lx/By	L70/B10
Operating temperature range [°C]	-40 ÷ 50
Driver	LED Driver

Mechanical parameters:

Assembly	ground
Material	aluminium
Color	anthracite
Diffuser	transparent glass lenses
Impact resistant	IK09
Dimensions [mm]	3000 x 150 x 100



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.

Date of last update: 25-04-2024