

Description

Basic information

Family: TULIP L

Product: **TULIP L 24t 3F WH 940 43 D90**

Index: **BLS0000012773**

Pictograms:












● Lighting and electrical parameters


| Light source | LED |
|-------------------------------------|---------------------|
| Luminous flux LED [lm] | 4979 |
| LED power [W] | 35.7 |
| Luminaire luminous flux [lm] | 4332 |
| Power of luminaire [W] | 39 |
| Luminaire's light efficiency [lm/W] | 111 |
| Color of the light [K] | 4000 |
| CRI | >90 |
| SDCM (LED sources) | 3 |
| Beam angle [°] | 24st |
| Protection against electric shock | 1 |
| Protection degree | IP20 |
| Voltage | 220-240 V, 50-60 Hz |
| Lifetime of LED sources [h] | 70000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 5÷30 |
| Driver | LED Driver |
| | |

Mechanical parameters:

| Assembly | 3-phase track |
|------------------|---------------|
| Material | aluminium |
| Color | white |
| Impact resistant | IKO4 |
| Dimensions [mm] | D90 x 190 |



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 14-05-2024

