

Description



Basic information

Family: **ASTER C**  
Product: **ASTER CC N PC OPAL IP65 840 72 1200**  
Index: **BLS0000013145**  
Pictograms:




Lighting and electrical parameters

Light source	LED
<b>Luminaire luminous flux [lm]</b>	<b>7200</b>
Power of luminaire [W]	50
<b>Luminaire's light efficiency [lm/W]</b>	<b>144</b>
Color of the light [K]	4000
<b>CRI</b>	<b>&gt;80</b>
SDCM (LED sources)	4
<b>Beam angle [°]</b>	<b>115</b>
Protection against electric shock	II
<b>Protection degree</b>	<b>IP65</b>
Voltage	220-240 V, 50-60 Hz
<b>Lifetime of LED sources [h]</b>	<b>70000</b>
Lx/By	L70/B50
<b>Operating temperature range [°C]</b>	<b>-20 - +40</b>
Driver	LED Driver

Mechanical parameters:

Assembly	ceiling mounted
<b>Material</b>	<b>polycarbonate</b>
Color	gray
<b>Diffuser</b>	<b>PC opalized polycarbonate</b>
Impact resistant	IK10
<b>Dimensions [mm]</b>	<b>1190 x 85 x 67</b>



A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality.  
Date of last update: 25-04-2024