



Description

FREESIA RT Surface mounted luminaire is made of varnished steel sheet. FREESIA RT luminaire is recommended for, among others, office areas, schools, universities, public administration buildings, and other objects of professional character.

Basic information

| | |
|-------------|--|
| Family: | FREESIA RT |
| Product: | FREESIA RT N MPRM+PLX GR 830 14 1150x100 |
| Index: | BLS0000013242 |
| Pictograms: | |



Lighting and electrical parameters

| | |
|---|-------------------|
| Light source | LED |
| Luminaire luminous flux [lm] | 1501 |
| Power of luminaire [W] | 13 |
| Luminaire's light efficiency [lm/W] | 115 |
| Color of the light [K] | 3000 |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Photobiological risk class (IEC/EN 62471) | RG0 |
| Protection against electric shock | I |
| Protection degree | IP20 |
| Voltage | 220-240V, 50-60Hz |
| Lifetime of LED sources [h] | 150000 |
| Lx/By | L80/B50 |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | LED driver |

Mechanical parameters:

| | |
|------------------|-----------------|
| Assembly | ceiling mounted |
| Material | steel sheet |
| Color | gray |
| Diffuser | MPRM microprism |
| Impact resistant | IK04 |
| Dimensions [mm] | 1150 x 100 x 50 |



A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 18-08-2025