



Description

PRIMROSE 3S N ceiling mounted luminaire made of aluminium, intended for ceiling mounting on the outside of the building. The luminaire shines in 3 directions, and thanks to that lights the whole area. This luminaire has an exchangeable light source with E27 base. PRIMROSE luminaire is recommended for its ingress protection (IP65), among others for balconies and terraces.

Basic information

Family:	PRIMROSE 3S N 250
Product:	PRIMROSE 3S N PLX ANT IP65 840 5 250
Index:	BLS0000013251
Pictograms:	




Lighting and electrical parameters

Light source	LED
Luminaire luminous flux [lm]	573
Power of luminaire [W]	4.6
Luminaire's light efficiency [lm/W]	125
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Protection against electric shock	I
Protection degree	IP65
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	72000
Lx/By	L80/B10
Operating temperature range [°C]	-30 ÷ +30
Driver	LED driver

Mechanical parameters:

Assembly	ceiling mounted
Material	aluminum
Color	anthracite
Diffuser	PLX opalized
Impact resistant	IK10
Weight [kg]	0.85
Dimensions [mm]	250 x 110 x 102



A graph of light