NEMESIA IN OD 205



Description

NEMESIA IN architectural outdoor luminaire is mounted in the wall with usage of mounting box. Body of NEMESIA IN luminaire is made of aluminium and painted with specialistic façade paint, resistant to atmospheric conditions. It is perfect for highlighting pavements, communication routes going alongside walls.

Basic information

Family: **NEMESIA IN OD 205**

Product: **NEMESIA IN OD RT WH IP65 840 6 205**

Index: BL\$0000013302

Pictograms:












● Lighting and electrical parameters

Light source	LED
Luminaire luminous flux [lm]	610
Power of luminaire [W]	4.5
Luminaire's light efficiency [lm/W]	136
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Protection against electric shock	1
Protection degree	IP65
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	72000
Lx/By	L80/B10
Operating temperature range [°C]	-25 ÷ 30
Driver	LED driver

Mechanical parameters:

Dimensions [mm]	205 x 107 x 65
Impact resistant	IK09
Diffuser	glass
Color	white
Material	aluminum
Assembly	wall-mounted



A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 17-09-2025

