



Description

Industrial luminaires ASTER is a ceiling luminary. It features high ingress protection (IP65) and high protection against mechanical impact (IK08). ASTER luminary is well-adjusted to dusty rooms or those with elevated humidity. ASTER luminaires are intended for rooms, such as halls, magazines, warehouses, subways, underground parking lots etc. ASTER should be exploited in temperature between -20°C and +40°C.

Basic information

Family: **ASTER C**
Product: **ASTER CC N PC OPAL IP65 840 50 1200**
Index: **BLS0000013543**
Pictograms:




Lighting and electrical parameters

| | |
|--|---------------------|
| Light source | LED |
| Luminaire luminous flux [lm] | 5040 |
| Power of luminaire [W] | 36 |
| Luminaire's light efficiency [lm/W] | 140 |
| Color of the light [K] | 4000 |
| CRI | >80 |
| SDCM (LED sources) | 4 |
| Beam angle [°] | 115 |
| Protection against electric shock | I |
| Protection degree | IP65 |
| Voltage | 220-240 V, 50-60 Hz |
| Lifetime of LED sources [h] | 70000 |
| Lx/By | L70/B50 |
| Operating temperature range [°C] | -20 - +40 |
| Driver | LED Driver |

Mechanical parameters:

| | |
|--------------------|----------------------------------|
| Assembly | ceiling mounted |
| Material | polycarbonate |
| Color | gray |
| Diffuser | PC opalized polycarbonate |
| Impact resistant | IK10 |
| Weight [kg] | 1.24 |
| Dimensions [mm] | 1190 x 72 x 61 |



A graph of light

Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 25-04-2024