



ORCHID PZ LINIA

Description

Surface-mounted luminary ORCHID is made out of anodized aluminium profile. ORCHID luminary is recommended for: office spaces, schools, universities or public administration buildings etc.

Basic information

Family:	ORCHID PZ LINIA
Product:	ORCHID PZ-1,5m MPRM BL 840 LINIA-S 79 2242
Index:	BLS0000014142
Pictograms:	



Lighting and electrical parameters

Light source	LED
Luminaire luminous flux [lm]	7988
Power of luminaire [W]	54.5
Luminaire's light efficiency [lm/W]	147
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220-240 V, 50-60 Hz
Lifetime of LED sources [h]	150000
Lx/By	L80/B50
Operating temperature range [°C]	5 ÷ 30
Driver	LED driver

Mechanical parameters:

Assembly	pendant – slings required
Material	aluminum
Color	black
Diffuser	MPRM micropism
Impact resistant	IK06
Dimensions [mm]	2242 x 60 x 72



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 01-08-2025