



Description

Basic information

Family: DAISY PRO  
Product: DAISY PRO P PLX WH IP20/65 840 68 596  
Index: BLS0000014134  
Pictograms:




Lighting and electrical parameters


|                                           |                       |
|-------------------------------------------|-----------------------|
| Light source                              | LED                   |
| Luminaire luminous flux [lm]              | 6784                  |
| Power of luminaire [W]                    | 43.1                  |
| Luminaire's light efficiency [lm/W]       | 157                   |
| Color of the light [K]                    | 4000                  |
| CRI                                       | >80                   |
| SDCM (LED sources)                        | 3                     |
| Photobiological risk class (IEC/EN 62471) | RG0                   |
| Protection against electric shock         | II                    |
| Protection degree                         | IP20/65               |
| Voltage                                   | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h]               | 100000                |
| Lx/By                                     | L80/B10               |
| Operating temperature range [°C]          | 5 ÷ 30                |
| Driver                                    | LED driver            |

Mechanical parameters:

|                  |                                   |
|------------------|-----------------------------------|
| Assembly         | recessed into the modular ceiling |
| Material         | aluminum                          |
| Color            | white                             |
| Diffuser         | PLX opalized                      |
| Impact resistant | IK04                              |
| Dimensions [mm]  | 596 x 596 x 34                    |



A graph of light



Technical data may be changed. Photos of the luminaires may differ from reality.  
Date of last update: 21-10-2025