




Description

HOYA luminaire is built from rectangular aluminium profiles that are galvanized. Simple flat shape creates elegantly presenting architectural element. Used LED light sources in this luminaire enables to realize majority of the projects. Application: paths in gardens/parks, entrances to the properties, public spaces.

Basic information

Family:	HOYA 2L
Product:	HOYA 2L G IP65 ANT 740 ST-M 2x82 3000x150x150
Index:	BLS0000014215
Pictograms:	




Lighting and electrical parameters


Light source	LED
Luminaire luminous flux [lm]	16422
Power of luminaire [W]	108
Luminaire's light efficiency [lm/W]	152
Color of the light [K]	4000
CRI	>70
SDCM (LED sources)	3
Protection against electric shock	I
Protection degree	IP65
Voltage	220-240V, 50-60Hz
Lifetime of LED sources [h]	102000
Lx/By	L90/B10
Operating temperature range [°C]	-40 ÷ 50
Driver	LED driver

Mechanical parameters:

Assembly	ground-mounted
Material	aluminum
Color	anthracite
Diffuser	transparent glass lenses
Impact resistant	IK09
Dimensions [mm]	3000 x 150 x 150



A graph of light




Technical data may be changed. Photos of the luminaires may differ from reality.


Date of last update: 18-08-2025

Accessories


Index	BLS0000005917
Name	Fundament 850



Index	BLS0000009053
Name	Komplet nakrętek montażowych słupa + kapturek maskujący czarnym - do B-50



Index	BLS0000016279
Name	HOYA G 150x100 - Cover ANT



Index	BLS0000009083
Name	Izolacyjne złącze bezpiecznikowe IZK-4-01

